

IMPULSE FRAMEMASTER NAILER

FEATURES

- **Impulse Gas Technology**
Portable, no need for a compressor or hoses
- **Tool Free Depth of Drive Adjustment**
Five notch adjustment
For accurate nail placement
- **50 to 90mm Nails**
Full range of 50 to 90mm nails in bright, galvanised, and stainless steel
- **Nail Lock Out Bar**
Protects timber and tool
- **Ergonomic Design**
Operator friendly, non-slip handgrip and trigger improves comfort and safety
- **Skew Nailing Teeth**
Helps to grip the timber to ensure positive placement of the fastener
- **Low Tool Actuation Pressure**
Reduces operator fatigue
- **Reversible Belt / Rafter Hook**
Increased convenience and safety



Product Code	Model Description	Barcode
B20540	IMPULSE FRAMEMASTER FRAMING NAILER	9315104013612

IMPULSE FRAMEMASTER NAILER

Specifications

Product Size (WxHxD)	368 x 310 x 100mm
Packaged Size (WxHxD)	450 x 450 x 140mm
Tool Weight (with battery)	3.4kg
Packaged Weight	5.9kg
Quantity Per Pack	1
Cycle Rate	2-3 Nails per second
Tool Duty Cycle Rate	1000 Nails per hour
Magazine Capacity	40 Nails
Nail Range Length	50 - 90mm
Nail Range Diameter	2.87 – 3.15mm
Battery	6 Volt DC (B20544E)
Battery Recharge Time	1.5 to 2 hours
Fuel Cell	Impulse – Twist n Lock - In Can – Long Fuel Cell
Propellant	Liquid Hydrocarbon
Fuel Cell & Battery Storage Temperature	Below 49° Celsius
Rated Input Voltage Battery Charger Base	12 Volt DC 800mA
Rated Output Voltage Battery Charger Base	6 Volt DC 750mA
Rated Input Voltage Power Adaptor	240 Volt AC 50/60 Hz
Rated Output Voltage Power Adaptor	12 Volt DC 800mA

CAPACITY

Battery Capacity	Up to 4,000 Nails per charge
Fuel Cell Capacity	Up to 1,200 Nails per charge