

IMPULSE IM90i BATTERY CHARGER KIT

FEATURES

- **Slim Line Power Input**
Vertical space saving power adapter
Saves space on a multi-socket power board
- **Switch Mode Technology**
Automatic shut down when the battery is not connected to save power
Battery protection circuitry to prevent over charging
- **Stable Charger Base**
Improved safety
- **LED Charge Indicator Lights**
Red light indicates battery requires charging
Green indicates battery is fully charged
Flashes between green and red when charging a very flat battery
- **Removable Battery Insert**
Designed for the Paslode Impulse® IM90i Battery (B30150)
Remove the insert and the charger base can be used with the standard Paslode Impulse® IM350 Battery (B20544E)



Product Code	Model Description	Barcode
B30200	IMPULSE IM90i BATTERY CHARGER KIT	9315104013827

IMPULSE IM90i BATTERY CHARGER KIT

Specifications

Adaptor Base Size (WxHxD)	70 x 50 x 117mm
Power Adaptor Size (WxHxD)	39 x 72 x 105mm
Packaged Size (WxHxD)	175 x 78 x 90mm
Product Weight	300g
Packaged Weight	342g
Quantity Per Pack	1
Battery	6 Volt DC / 1.5Ah (B30150)
Battery Recharge Time	1.5 hours
Rated Input Voltage Battery Charger Base	12 Volts DC 800mA
Rated Output Voltage Battery Charger Base	6 Volts DC 700mA
Rated Input Voltage Power Adaptor	230 Volt AC 50 to 60Hz
Rated Output Voltage Power Adaptor	12 Volt DC 800mA
Battery Capacity	Up to 4,000 nails per charge

Information presented in this product information sheet is believed to be accurate and reliable, no responsibility for inaccuracies can be assumed by Paslode. Paslode reserves the right at any time to change performance characteristics without prior notice.
Paslode New Zealand Limited, 38 Canaveral Drive, Albany, Auckland. P.O.Box 100 303, North Shore Mail Centre, Auckland

(Note: This Product information sheet is not intended for distribution to end users) - B30200 Battery Charger Kit IM90i 09/08 v1

READ ALL SAFETY INSTRUCTIONS