

IMPULSE IM90i NO MAR(k) GUIDE

FEATURES

- **Replaceable Rubber Contact Tip**
Prevents damage to timber and cladding surfaces
Improves aesthetic appearance of all timber surfaces
Ideally suited to decking and cladding applications
- **Die-cast Steel Construction**
Superior durability for long life
High impact resistance for long life
- **Eight Depth Settings**
Easy thumb wheel depth of drive gauge gives greater control over drive settings for a superior finish
Ideal for a variety of fastening applications including:
 - Plywood cladding
 - Pine weatherboard cladding
 - Pine decking
 - Fibre Cement Board / Cladding



Product Code	Model Description	Barcode
B30300	IMPULSE IM90i NO MAR(K) GUIDE	3439510132111

Specifications	
Product Size (WxHxD)	38 x 30 x 65mm
Packaged Size (WxHxD)	90 x 140 x 50mm
Product Weight	72g
Packaged Weight	90g

Information presented in this product information sheet is believed to be accurate and reliable, no responsibility for inaccuracies can be assumed by Paslode. Paslode reserves the right at any time to change performance characteristics without prior notice.
Paslode New Zealand Limited, 38 Canaveral Drive, Albany, Auckland. P.O.Box 100 303, North Shore Mail Centre, Auckland

(Note: This Product information sheet is not intended for distribution to end users) - B30300 No Mar(K) Guide IM90i 09/08 v1

READ ALL SAFETY INSTRUCTIONS