

Paslode® FrameMaster-Li™ Framing Nailer

Paslode Impulse Gas Technology

Portable, no need for heavy compressors or awkward air lines

Lithium-Ion Battery Technology

Up to 6,000 nails per charge

Charge in 1 hour

Low Tool Actuation Pressure

Reduces operator fatigue

Tool-Free Depth of Drive Adjustment

Five depth of drive settings

Greater flexibility for nail placement and a superior finish



Two Lithium-Ion batteries included with tool

Suitable for 44 to 90mm Length Nails

Full range of 50 to 90mm nails in bright, galvanised, and stainless steel

Product Nail Guide attachment (B20540P) required to drive 44mm product nails

Suitable for 2.8 to 3.15mm Diameter Nails

Nail Lock Out Bar

Eliminates blank tool firing

Protects timber and tool

Optimum Skew Nailing Teeth Placement

Helps grip timber to ensure positive placement of the fastener

Ergonomic Design

Operator friendly

Non-slip handgrip and trigger improves comfort and safety

On / Off Battery Positions

Improved safety and battery conservation

Reversible Belt and Rafter Hook

Safely secures tool on timber framing

Secures tool on tool belt for convenience



Product Code

Model Description

Barcode

B20543

Paslode Impulse IM325 2.8 - 3.15mm FrameMaster-Li Framing Nailer

9315104015746



Impulse® FrameMaster-Li™ Framing Nailer

Specifications

Product Size (WxHxD)	368 x 310 x 100mm
Packaged Size (WxHxD)	450 x 450 x 140mm
Tool Weight (with battery)	3.3kg
Packaged Weight	5.8kg
Quantity Per Pack	1
Cycle Rate	2-3 nails per second
Tool Duty Cycle Rate	1000 shots per hour
Magazine Capacity	40 nails (1 strip)
Nail Range Length	50 – 90mm
Nail Range Diameter	2.87 – 3.15mm
Battery	7.4 Volt DC 1250mAh Lithium-Ion (B20544E)
Battery Recharge Time	1 hour
Fuel Cell	Paslode Impulse Fuel Cell Quick Load
Propellant	Liquid Hydrocarbon
Fuel Cell & Battery Storage Temperature	Below 49°C
Rated Input Voltage Battery Charger Base	12 Volt DC @ 1.8A
Rated Output Voltage Battery Charger Base	8.5 Volt DC @ 2.0A
Rated Input Voltage Power Adaptor	240 Volt AC 50 to 60Hz 30W
Rated Output Voltage Power Adaptor	12 Volt DC 1.8A

Capacity

Battery Capacity	Up to 6,000 nails per charge
Fuel Cell Capacity	Up to 1,200 nails per cell

The information presented in this product information sheet is correct as at the date of publication. Paslode reserves the right to change performance, product or content information without notice.

Read all safety instructions