

Special Fixing Applications



CHH Woodproducts & Paslode Nail Matrix of acceptable fixing solutions

Refer to CHH technical literature for further information to ensure correct product specification for your application.



50 x 2.87mm RounDrive Hot Dip Galv Ring Nail
B20557

60 x 2.87mm PlyGrip RounDrive Hot Dip Galv Ring Nail
B20575V

65 x 2.87mm RounDrive Hot Dip Galv Ring Nail
B20558

75 x 3.06mm RounDrive Hot Dip Galv Ring Nail
B20564

55 x 2.8 Round Head Stainless Steel (Bracing) Ring
Nail B20572

75 x 3.06mm RounDrive Stainless Steel Ring Nail
B20573

Ecoply bracing untreated 7mm/9mm/12mm



Ecoply bracing H3 CCA 7mm/9mm/12mm



Shadowclad (direct fixed)*



Shadowclad (fixed to 20mm cavity battens)*



Shadowclad (direct fixed)**



Shadowclad (fixed to 20mm cavity battens)***



Shadowclad (fixed to 20mm cavity battens)****



Batten, Structural Timber (BRANZ Tested)
(See BRANZ Guideline September 2004)



- Adjust work contact element and drive nails flush with plywood surface.
- Care should be taken with the placement of the nail.
- For best results nails should be driven at 90 degrees to the work face.

* Not sea spray zone and not structural bracing

** Sea spray zone and / or structural bracing

*** Sea spray zone and / or structural bracing. Cavity battens structurally fixed

**** Sea spray zone and / or structural bracing. Cavity battens fixed in accordance with E2/ASI